

DECLARATION OF PERFORMANCE

No 1071-CPD-1018

1. Unique identification code of the product-type:
Hunton Vindtett (12, 15, 19 og 25 mm)
Hunton Bitroc (12, 15, 19 og 25 mm)
Hunton Stubbeloft (12 og 18 mm)
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
SB.HLS
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Wood-based panels for use in construction
4. Name and contact address of the manufacturer as required under Article 11(5):
Hunton Fiber AS
Po Box 633
NO-2810 GJØVIK, Norway
5. Where applicable, name and contact address of the authorized representative, specified in Article 12 (2):
Contact the manufacturer
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
System 2+
7. In case of declaration of performance concerning a product covered by a harmonized standard
EN 13986:2004 Annex ZA SINTEF Byggforsk
EU-Notified Body No 1071
8. Not applicable
- 9.

Essential characteristics	Performance	Harmonized technical specification
Air permeability of the material	$\leq 0,008 \text{ m}^3/\text{m}^2\text{hPa}$	EN 13986:2004
Air permeability as wall sheathing	$0,014 \text{ m}^3/\text{m}^2\text{hPa}$	EN 13986:2004
Water vapour resistance	$sd \leq 0,2 \text{ m}$	EN 13986:2004
Moisture movement	0,3 %	EN 13986:2004
Thickness swelling	$\leq 5 \%$	EN 13986:2004
Water absorption	$\leq 30 \%$	EN 13986:2004
Thermal resistance	$0,25 \text{ m}^2\text{K/W}$	EN 13986:2004
Bending strength	$\geq 1,6 \text{ N/mm}^2$	EN 13986:2004
E-modulus in bending	$\geq 170 \text{ N/mm}^2$	EN 13986:2004
Racking resistance	2,0-3,3 kNm	EN 13986:2004

10. The performance of the product identified in 1 and 2 is in conformity with the performance in 9

Lars Harald Nilsen, QA & HES Mngr

GJØVIK 08.05.13

Place/Date


 HUNTON FIBER AS