

Declaration of performance acc. Regulation EU No. 305/2011 (CPR) No. P2-CPR-2013-07-01-1 – PB P2

SIA "KRONOSPAN Riga"
Gubernciems 7, Rīga, LV-1016, Latvia
Tel.: +371 67 430 147, Fax: +371 67 430 167
Id. N°: 40003774690, VAT N°: LV40003774690
office@ kronospan-riga.lv, www. kronospan-riga.lv

DECLARATION OF PERFORMANCE No. P2-CPR-2013-07-01-1

1. Unique identification code of the product-type:

Particleboard PB P2

2. Identification of the product:

PB P2

Identification code is printed on the each board and consists of production plant, product type, production date and time; and/or is printed on the label attached to the production boards packing.

3. Intended use or uses of the product:

For internal use as a non-structural component (including furniture) in dry conditions (P2 acc. EN 312 is non load-bearing boards for use in dry conditions)

4. Name and contact address of the manufacturer:

SIA "KRONOSPAN Riga"
Gubernciems 7
LV-1016, Riga
Latvia
Business ID 40 003 774 690
www.kronospan-riga.lv

5. System of assessment and verification of constancy of performance:

System 4



Declaration of performance acc. Regulation EU No. 305/2011 (CPR) No. P2-CPR-2013-07-01-1 – PB P2

6. Declared performance

| Essential characteristics | Performance | | | | | Harmonised technical |
|--|---|-----------|-----------|-----------|-----------|-------------------------|
| | Boards thickness in mm | | | | | |
| | 8 – 13 | > 13 - 20 | > 20 - 25 | > 25 - 32 | > 32 - 40 | specification |
| Bending strength ¹ acc. EN 310 | 11 MPa | 11 MPa | 10,5 MPa | 9,5 MPa | 8,5 MPa | |
| Bending stiffness ¹ (Modulus of elasticity) acc. EN 310 | 1800 MPa | 1600 MPa | 1500 MPa | 1350 MPa | 1200 MPa | |
| Tensile strength (Internal bond) acc. EN 319 | 0,40 MPa | 0,35 MPa | 0,30 MPa | 0,25 MPa | 0,20 MPa | |
| Release of content of formaldehyde acc. EN 120 | Class E1 (≤ 8 mg/ 100g oven dry board) | | | | | EN 13986:2004 |
| Reaction to fire acc. EN 13501-1 | NPD | | | | | |
| Water vapour permeability | NPD | | | | | |
| Airborne sound insulation | NPD | | | | | |
| Sound absorption | NPD | | | | | |
| Thermal conductivity | NPD | | | | | |
| Strength and stiffness for structural use | NPD | | | | | |
| Mechanical durability | NPD | | | | | |
| Biological durability acc. EN 353 | NPD | | | | | |
| Release (Content) of pentachlorophenol (PCP) | NPD | | | | | |

¹ The table values of strength are not characteristic values for use in the design of wood framed structures (e.g. according to EN 1995-1-1).

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Janīna Mitrofanova Member of the Board

Ivars Plaudis Technical Director

Riga, 18.10.2013